Effective ave Jan. 1, 2023

Menu Item	Model #	Audio Decoding																																			
Subcategory	Appearance	Physical	Packaging	Physical packaging	Web	Key Pages	Appearance	Server	Performance	Physical depth	Unit	Power / Thermal	Cable Info	Unit	Unit	Unit	Unit Retail Package	Power Input	Power Consumption	Mounting	Application	Power Adapter Included?	Accessory Kit				Ports	Unit	Unit	#	Picture	Unit Retail	Notes
VR/MR	VMP	PRELOVEPORT-US-wt	1000x1000 (GMP)	1000x1000 (GMP) 1000 (W) x 1000 (L) x 1000 (H) mm 1000 x 1000 x 1000 mm 1000 x 1000 mm	1000 (W) x 1000 (L) x 1000 (H) mm 1000 x 1000 x 1000 mm 1000 x 1000 mm	No	1000(L) x 1000 (W) MM	120° (1920)	1701-1800 Votes	3840×2160 Pixels Native Resolution Native Resolution	mm	Ref Rate (1 - 240Hz)	0.5m 1.5GHz (4) (Gold)	No	No	No	840×840×2600(3000) Cust Unit	84/20/1200	Max: 100 W, 84/20/1200 Suggested Power: 45 W 1.5 GHz (4) (Gold)	1 Year	Operating Temperature 41°F ~ 104°F (5 ~ 40°C) Storage Temperature -4°F ~ 140°F (-20 ~ 60°C) Operating Humidity 20% ~ 80% (Non-condensing) Storage Humidity 5% ~ 90% (Non-condensing)	No	1000(W) 1000(L) Cust Unit mm mm				Digital: 1 DISPLAY(1.2)(DISPLAY)	Yes	Yes	0	0.000		
		PRELOVEPORT-US-wt	1000x1000 (GMP)	1000x1000 (GMP) 1000 (W) x 1000 (L) x 1000 (H) mm 1000 x 1000 x 1000 mm 1000 x 1000 mm	1000 (W) x 1000 (L) x 1000 (H) mm 1000 x 1000 x 1000 mm 1000 x 1000 mm	No	1000(L) x 1000 (W) MM	120° (1920)	1701-1800 Votes	3840×2160 Pixels Native Resolution Native Resolution	mm	Ref Rate (1 - 240Hz)	0.5m 1.5GHz (4) (Gold)	No	No	No	840×840×2600(3000) Cust Unit	84/20/1200	Max: 100 W, 84/20/1200 Suggested Power: 45 W 1.5 GHz (4) (Gold)	1 Year	Operating Temperature 41°F ~ 104°F (5 ~ 40°C) Storage Temperature -4°F ~ 140°F (-20 ~ 60°C) Operating Humidity 20% ~ 80% (Non-condensing) Storage Humidity 5% ~ 90% (Non-condensing)	No	84/20/1200 1000x1000 Cust Unit mm mm				Digital: 1 DISPLAY(1.2)(DISPLAY)	Yes	Yes	0	0.000		
		PRELOVEPORT-US-wt	1000x1000 (GMP)	1000x1000 (GMP) 1000 (W) x 1000 (L) x 1000 (H) mm 1000 x 1000 x 1000 mm 1000 x 1000 mm	1000 (W) x 1000 (L) x 1000 (H) mm 1000 x 1000 x 1000 mm 1000 x 1000 mm	No	1000(L) x 1000 (W) MM	120° (1920)	1701-1800 Votes	3840×2160 Pixels Native Resolution Native Resolution	mm	Ref Rate (1 - 240Hz)	0.5m 1.5GHz (4) (Gold)	No	No	No	840×840×2600(3000) Cust Unit	84/20/1200	Max: 100 W, 84/20/1200 Suggested Power: 45 W 1.5 GHz (4) (Gold)	1 Year	Operating Temperature 41°F ~ 104°F (5 ~ 40°C) Storage Temperature -4°F ~ 140°F (-20 ~ 60°C) Operating Humidity 20% ~ 80% (Non-condensing) Storage Humidity 5% ~ 90% (Non-condensing)	No	84/20/1200 1000x1000 Cust Unit mm mm				Digital: 1 DISPLAY(1.2)(DISPLAY)	Yes	Yes	0	0.000		
		PRELOVEPORT-S-[DEMO]	1000x1000 (GMP)	1000x1000 (GMP) 1000 (W) x 1000 (L) x 1000 (H) mm 1000 x 1000 x 1000 mm 1000 x 1000 mm	1000 (W) x 1000 (L) x 1000 (H) mm 1000 x 1000 x 1000 mm 1000 x 1000 mm	No	1000(L) x 1000 (W) MM	120° (1920)	1701-1800 Votes	3840×2160 Pixels Native Resolution Native Resolution	mm	Ref Rate (1 - 240Hz)	0.5m 1.5GHz (4) (Gold)	No	No	No	840×840×2600(3000) Cust Unit	84/20/1200	Max: 100 W, 84/20/1200 Suggested Power: 45 W 1.5 GHz (4) (Gold)	1 Year	Operating Temperature 41°F ~ 104°F (5 ~ 40°C) Storage Temperature -4°F ~ 140°F (-20 ~ 60°C) Operating Humidity 20% ~ 80% (Non-condensing) Storage Humidity 5% ~ 90% (Non-condensing)	No	84/20/1200 1000x1000 Cust Unit mm mm				Digital: 1 DISPLAY(1.2)(DISPLAY)	Yes	Yes	0	0.000		
		PRELOVE	1000x1000 (GMP)	1 Wireless	1000 Pcs	No	1000(L) x 1000 (W) MM	120° (1920)	1701-1800 Votes	3840×2160 Pixels Native Resolution Native Resolution	mm	Ref Rate (1 - 240Hz)	0.5m 1.5GHz (4) (Gold)	No	No	No	840×840×2600(3000) Cust Unit	84/20/1200	Max: 100 W, 84/20/1200 Suggested Power: 45 W 1.5 GHz (4) (Gold)	1 Year	Operating Temperature 41°F ~ 104°F (5 ~ 40°C) Storage Temperature -4°F ~ 140°F (-20 ~ 60°C) Operating Humidity 20% ~ 80% (Non-condensing) Storage Humidity 5% ~ 90% (Non-condensing)	No	84/20/1200 1000x1000 Cust Unit mm mm				Digital: 1 DISPLAY(1.2)(DISPLAY)	Yes	Yes	0	0.000		
		PRELOVE-HP	1000x1000 (GMP)	1 Wireless	1000 Pcs	No	1000(L) x 1000 (W) MM	120° (1920)	1701-1800 Votes	3840×2160 Pixels Native Resolution Native Resolution	mm	Ref Rate (1 - 240Hz)	0.5m 1.5GHz (4) (Gold)	No	No	No	840×840×2600(3000) Cust Unit	84/20/1200	Max: 100 W, 84/20/1200 Suggested Power: 45 W 1.5 GHz (4) (Gold)	1 Year	Operating Temperature 41°F ~ 104°F (5 ~ 40°C) Storage Temperature -4°F ~ 140°F (-20 ~ 60°C) Operating Humidity 20% ~ 80% (Non-condensing) Storage Humidity 5% ~ 90% (Non-condensing)	No	84/20/1200 1000x1000 Cust Unit mm mm				Digital: 1 DISPLAY(1.2)(DISPLAY)	Yes	Yes	0	0.000		
		PRELOVE-HP-WCS-PANIC	1000x1000 (GMP)	1 Wireless	1000 Pcs	No	1000(L) x 1000 (W) MM	120° (1920)	1701-1800 Votes	3840×2160 Pixels Native Resolution Native Resolution	mm	Ref Rate (1 - 240Hz)	0.5m 1.5GHz (4) (Gold)	No	No	No	840×840×2600(3000) Cust Unit	84/20/1200	Max: 100 W, 84/20/1200 Suggested Power: 45 W 1.5 GHz (4) (Gold)	1 Year	Operating Temperature 41°F ~ 104°F (5 ~ 40°C) Storage Temperature -4°F ~ 140°F (-20 ~ 60°C) Operating Humidity 20% ~ 80% (Non-condensing) Storage Humidity 5% ~ 90% (Non-condensing)	No	84/20/1200 1000x1000 Cust Unit mm mm				Digital: 1 DISPLAY(1.2)(DISPLAY)	Yes	Yes	0	0.000		
	VMP	PRELOVE	1000x1000 (GMP)	1 Wireless	1000 Pcs	No	1000(L) x 1000 (W) MM	120° (1920)	1701-1800 Votes	3840×2160 Pixels Native Resolution Native Resolution	mm	Ref Rate (1 - 240Hz)	0.5m 1.5GHz (4) (Gold)	No	No	No	840×840×2600(3000) Cust Unit	84/20/1200	Max: 100 W, 84/20/1200 Suggested Power: 45 W 1.5 GHz (4) (Gold)	1 Year	Operating Temperature 41°F ~ 104°F (5 ~ 40°C) Storage Temperature -4°F ~ 140°F (-20 ~ 60°C) Operating Humidity 20% ~ 80% (Non-condensing) Storage Humidity 5% ~ 90% (Non-condensing)	No	84/20/1200 1000x1000 Cust Unit mm mm				Digital: 1 DISPLAY(1.2)(DISPLAY)	Yes	Yes	0	0.000		

Subcategory	Appearance	Physical	Packaging	Physical packaging	Web	Key Pages	Appearance	Server	Performance	Physical depth	Unit	Power / Thermal	Cable Info	Unit	Unit	Unit	Unit Retail Package	Power Input	Power Consumption	Mounting	Application	Power Adapter Included?	Accessory Kit	Compatibility	Unit	Unit	Ports	Unit	Unit	#	Picture	Unit Retail	Notes
Vmax		VMAX-HP		Cust			1 Cable, 2 Color		Yes										Max 1000 W, 2.5 Years Warranty		Operating Temperature 41°F ~ 104°F (5 ~ 40°C) Storage Temperature -4°F ~ 140°F (-20 ~ 60°C) Operating Humidity 20% ~ 80% (Non-condensing) Storage Humidity 5% ~ 90% (Non-condensing)																		